

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1851269.060 Y=75607.110				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-120				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -24.3 Ft.			
9. TOTAL DEPTH OF HOLE 19.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.3	.0					-24.3	0
			Light gray medium to fine quartz sand, few thin layers of dark gray shell fragments in fine gravel range, scattered shell fragments and whole shells in medium gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100	1.0		2.5
						-28.3	5
-31.7	7.4		Light gray fine quartz sand, few scattered whole shells and shell fragments in fine to coarse gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100	8.0		7.5
						-34.3	10
				100			12.5
						-38.3	15
-42.2	17.9			100	16.0		17.5
						Large whole shell at 17.6 ft.	
-43.5	19.2		Light tannish gray fine quartz sand, silt and clay inclusions. 10 YR 7.5/1-7.5/1.5 (SP)				
-43.9	19.6		Tannish gray silty quartz sand. 10 YR 6.5/2 (SM)			-43.9 Composite 0-16.0 ft.	20
						Final 4/15/03	
							22.5