

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE	
2. LOCATION (Coordinates or Station) X=1851511.340 Y=73486.350			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW	
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE	
4. HOLE NO. (As shown on drawing title and file number) BC-122			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 2 undisturbed: 0	
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2	
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER	
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02	
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -25.3 Ft.	
9. TOTAL DEPTH OF HOLE 19.6 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %	
			19. SIGNATURE OF G. Zarillo, SEA, Inc.	

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.3	.0					-25.3	0
-26.4	1.1		Light gray medium to fine quartz sand, very abundant large gray to tan whole shells in medium to coarse gravel range. 10 YR 7.5/0.5 (SW)		10		
			Light gray fine quartz sand, scattered gray shell fragments in fine to medium gravel range, few inclusions of silt and clay in collapsed burrow structures. 10 YR 7.5/0.5 (SP)	100			2.5
						-30.3	5
				100	80		7.5
						-35.3	10
-37.8	12.5		Tannish gray fine quartz sand, some silt. 10 YR 7.5/1-7.5/1.5 (SP)	100			12.5
-38.6	13.3		Gray silty sand, some plastic clay. 10 YR 6/0.5 (SM)			-40.3	15
				100			17.5
-44.9	19.6					-44.9 Composite 0-10.0 ft.	20
						Final 6/25/03	
							22.5