

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1866626.290 Y=76220.540				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-125R1-R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.7 Ft.			
9. TOTAL DEPTH OF HOLE 13.5 Ft.				18. TOTAL CORE RECOVERY FOR BORING 84 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.7	.0					-29.7	0
-30.4	.7		Tan medium to fine quartz sand, gray to tan shell fragments and whole shells in medium to coarse gravel range. 10 YR 7.5/2 (SP)				
			Medium to light gray fine quartz sand, dark gray shell fragments in medium to coarse gravel range, trace of silt and clay in burrow structures. 10 YR 7.5/0.5-7/0.5 (SP)	100			2.5
-34.7	5.0					-34.7	5
-36.1	6.4		Tannish gray medium to fine quartz sand, large shell fragments and whole shells in medium to coarse gravel range. 10 YR 7.5/2 (SP)			Large shell fragments at 6.2-6.4 ft.	
			Dark gray silty quartz sand, abundant clay, few large white to tan shell fragments and whole shells in coarse gravel range. 10 YR 5.5/0.5 (SM)	100			7.5
						Gap between 125R1 and	
						-39.7	10
						125R2 at 9.6-10.8 ft.	
				100			12.5
-43.2	13.5					-43.2	15
						Composite 0-5.0 ft.	20
						Final 5/1/03	22.5