

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1869026.550 Y=65990.770				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-126				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -35.5 Ft.			
9. TOTAL DEPTH OF HOLE 15.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 77 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-35.5	.0					-35.5	0
-36.7	1.2		Dark gray silty sand, abundant large shell fragments and whole shells. 10 YR 5.5/0.5 (SM)				
-38.0	2.5		Medium gray fine quartz sand, some silt. 10 YR 7/0.5 (SP)				
			Medium to dark gray silty quartz sand, some clay. 10 YR 5.5/0.5-6/0.5 (SM)	100			2.5
-40.4	4.9		Dark gray silty quartz sand, abundant clay. 10 YR 5.5/0.5 (SM)			-40.5	5
				100			7.5
-45.6	10.1		Dark gray silt and clay. 10 YR 5.5/0.5 (ML)			-45.5	10
				100			12.5
-50.7	15.2					-50.7	15
							17.5
						No samples	20
						Final 5/22/03	22.5