

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1876038.640 Y=77605.650				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-127				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 1 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.8 Ft.			
9. TOTAL DEPTH OF HOLE 18.8 Ft.				18. TOTAL CORE RECOVERY FOR BORING 99 %			
				18. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.8	.0		Gray to light gray medium to fine quartz sand, abundant dark gray to gray shell fragments in fine to medium gravel range. 10 YR 7/0.5-7.5/0.5 (SP)	100	3.0	-30.8	0
-34.4	3.6		Medium gray very fine quartz sand and silt, shell fragments and whole shells in medium gravel range. 10 YR 7/0.5-7/1 (SM)			-35.8	5
-36.9	6.1		Gray to brownish gray fine quartz sand. 10 YR 7/0.5-7/1.5 (SM)	100		-40.8	10
-44.0	13.2		Gray to tannish gray fine quartz sand, abundant silt. 10 YR 7/0.5-7/2 (SP)	100		-45.8	15
-48.6	18.8					-49.6	20
						No composite	20
						Final 5/1/03	20
							22.5