

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1878005.750 Y=67972.040				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-128				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -32.8 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-32.8	.0					-32.8	0
			Light tannish gray fine quartz sand, abundant white to dark gray shell fragments in fine to medium gravel range. 10 YR 7.5/1-7.5/1.5 (SP)	100			2.5
-35.6	2.8						
			Medium to light gray fine quartz sand, abundant gray to white shell fragments in medium gravel range, trace of silt. 10 YR 7/0.5-7.5/0.5 (SP)				
-37.1	4.3					-37.8	5
			Dark gray silty quartz sand. 10 YR 5.5/0.5 (SM)				
-38.8	6.0			100		Large whole shells in lag deposit at 5.7-6.7 ft.	7.5
			Dark gray silty sand, few large shell fragments. 10 YR 6/0.5 (SM)				
-41.7	8.9						10
			Tannish gray silt, some quartz sand. 10 YR 6.5/2 (ML)			-42.8	
-44.6	11.8			100			12.5
			Dark gray silt. 10 YR 5.5/0.5 (ML)				
				100		-47.8	15
-51.9	19.1						17.5
						-51.9	20
						No samples	
						Final 5/22/03	
							22.5