

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1894001.130 Y=59975.650				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-130				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -37.0 Ft.			
9. TOTAL DEPTH OF HOLE 18.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 92 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-37.0	.0					-37.0	0
			Light gray fine quartz sand, abundant gray shell fragments in fine gravel range, scattered large shell fragments and whole shells in medium to coarse gravel range. 10 YR 7.5/0.5 (SP)	100			2.5
-40.6	3.6		Gray silt, large white oyster shells. 10 YR 5/0.5 (ML)			Large wood fragment at 3.7 ft.	
						-42.0	5
-43.3	6.3		Gray to grayish orange silt. 10 YR 6/0.5-6/3.5 (ML)				
-44.6	7.6		Gray silt. 10 YR 6/0.5 (ML)	100			7.5
						-47.0	10
						Layer of decayed wood	
						at 10.6-10.9 ft.	
				100			12.5
-52.4	15.4		Gray clay and silt. 10 YR 5/0.5 (CL)			-52.0	15
-55.2	18.2			100		-55.2	17.5
						No samples	20
						Final 5/22/03	
							22.5