

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1919029.320 Y=83991.970				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-132				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.9 Ft.			
9. TOTAL DEPTH OF HOLE 17.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.9	.0					-30.9	0
-33.0	2.1		Light gray fine quartz sand. 10 YR 8/0.5 (SP)	100	1.0		2.5
-35.8	5.0		Medium gray fine quartz sand, some silt. 10 YR 7/0.5-6.5/0.5 (SP)			-35.8	5
			Very light tannish gray to white fine quartz sand. 10 YR 8/1-9/0.5 (SP)	100	8.0		7.5
-41.8	10.9		Light gray medium to fine quartz sand. 10 YR 7.5/0.5 (SP)	100	12.0	-40.8	10
-45.1	14.2		Medium light tannish gray quartz sand. 10 YR 7.5/1 (SP)			-45.8	15
-47.0	16.1		Brownish gray medium to coarse quartz sand, some silt, abundant shell fragments in fine to coarse gravel range. 10 YR 6/1 (SP)				
-48.0	17.1		Brownish gray silty sand, shell fragments. 10 YR 6/1 (SM)	100			17.5
			Gray plastic silt and clay, some iron staining. 10 YR 5.5/0.5 (CL)				
-51.1	20.2					-51.1	20
						Composite 0-13.0 ft.	
						Final 4/1/03	