

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X-1918507.600 Y-83487.120				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-133				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-16-02 12-16-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.7 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 99 %			
				19. SIGNATURE OF G. Zarito, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.7	.0					-29.7	0
-30.8	1.1		Light gray fine quartz sand. 10 YR 8/0.5 (SP)				
			Light gray fine quartz sand, few gray shell fragments in medium gravel range. 10 YR 7.5/0.5 (SP)	100	10		
-32.8	3.1		Medium gray to tannish gray fine quartz sand, some silt. 10 YR 7/1-7.5/0.5 (SP)				
-34.2	4.5		Light gray fine quartz sand, scattered inclusions of decayed organic matter. 10 YR 7.5/0.5-8/0.5 (SP)			-34.7	5
-36.6	6.9		Very light gray to white fine quartz sand. 10 YR 8.5/0.5-9/0.5 (SP)	100	80		7.5
						-38.7	10
				100		Thin layer of wood fragments at 11.0 ft.	12.5
-44.8	15.1		Light gray medium to fine quartz sand. 10 YR 7.5/1.0 (SP)		150	-44.7	15
-46.5	16.8		Dark gray silty quartz sand, abundant white shells and shell fragments in medium to coarse gravel range. 10 YR 5/0.5 (SM)	100			17.5
-48.6	18.9		Brownish gray plastic clay. 10 YR 6/1.5 (CL)			-48.8	20
						Composite 0-15.0 ft.	
						Final 4/1/03	