

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1912502.530 Y=85013.360				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-136				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.2 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.2	.0					-26.2	0
-28.3	2.1		Light gray to tannish gray fine quartz sand, trace of white shell fragments in fine gravel range. 10 YR 8/0.5-8/1 (SP)				
			Very light gray to white fine quartz sand, abundant gray to white shell fragments and whole shells in fine to coarse gravel range. 10 YR 8/0.5-9/0.5 (SP)	100			2.5
						-31.2	5
-34.2	8.0			100			7.5
			Very light gray to white fine quartz sand, few scattered gray to white shell fragments in fine to medium gravel range. 10 YR 8/0.5-9/0.5 (SP)			-36.2	10
				100			12.5
						-41.2	15
				100			17.5
-45.3	19.1					-45.3	
						Composite 0-17.0 ft.	20
						Final 5/13/03	
							22.5