

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1912488.260 Y=83485.750				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-137				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -29.6 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-29.6	.0					-29.6	0
-30.8	1.3		Light tannish gray fine quartz sand, decayed worm tubes. 10 YR 8/1.5 (SP)				
			Light gray fine quartz sand, abundant large shell fragments and whole shells in medium to coarse gravel range. 10 YR 7.5/0.5-8/0.5 (SP)	100			2.5
-34.4	4.8		Very light gray fine quartz sand, trace of white shell fragments in fine to medium gravel range, trace of silt in burrow structures. 10 YR 8.5/0.5 (SP)			-34.6	5
				100			7.5
-41.8	12.2					-38.6	10
-42.2	12.6		Tan medium to fine quartz sand, trace of silt. 10 YR 7.5/2 (SP)	100			12.5
			Dark gray clay. 10 YR 5/0.5 (CL)			-44.6	15
-46.2	16.6		Orange-iron stained clay. 10 YR 7/4 (CL)	100			17.5
-48.2	18.6					-48.2	
						Composite 0-10.0 ft.	20
						Final 5/1/03	
							22.5