

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1912005.820 Y=85030.930				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-139				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -28.2 Ft.			
9. TOTAL DEPTH OF HOLE 20.2 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-28.2	.0		Gray to light gray fine quartz sand, very abundant tan to gray large whole shells and shell fragments in fine to coarse gravel range, gray silt and clay in burrow structures. 10 YR 7/0.5-7.5/0.5 (SP)	100		-28.2	0
-33.8	5.8		Light gray fine quartz sand, scattered gray to white shell fragments in fine to medium gravel range. 10 YR 8/0.5 (SP)	100		-33.2	5
-34.5	6.3		Very light gray to white fine quartz sand, scattered white shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100			7.5
-38.2	11.0		Light gray fine quartz sand mixed with large shell fragments. 10 YR 8.5/0.5 (SW)	100		-38.2	10
-38.8	11.7		White fine quartz sand, scattered layers and inclusions of white shell fragments in fine gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100			12.5
				100		-43.2	15
-48.1	19.9		Gray silt. 10 YR 5/1 (ML)				20
-48.4	20.2					-48.4	20
						Composite 0-18.0 ft.	
						Final 5/13/03	
							22.5