

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1916730.890 Y=86043.510				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-143				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.1 Ft.			
9. TOTAL DEPTH OF HOLE 19.3 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.1	.0					-30.1	0
-30.8	.7		Gray silt and sand. 10 YR 7/1 (SM)				
			Gray to dark gray silt, clay and fine quartz sand. 10 YR 6/0.5-7/0.5 (ML)	100			2.5
-33.1	3.0		Gray clay and silt. 10 YR 6.5/0.5-7/0.5 (CL)			-35.1	5
				100			7.5
-40.1	10.0		Gray silty sand. 10 YR 6.5/0.5-7/0.5 (SM)			-40.1	10
				100			12.5
-43.6	13.5		Light tannish gray fine quartz sand. 10 YR 7.5/1 (SP)			-45.1	15
-46.2	16.1		Brownish gray fine quartz sand, some silt. 10 YR 6/3 (SP)				
-46.8	16.7		Light gray fine quartz sand. 10 YR 8/0.5 (SP)	100			17.5
-48.4	19.3					-48.4	20
						No samples	
						Final 5/22/03	
							22.5