

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1918473.560 Y=85499.880				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-144				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -30.6 Ft.			
9. TOTAL DEPTH OF HOLE 17.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 89 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-30.6	.0					-30.6	0
-32.2	1.6		Light gray fine quartz sand. 10 YR 7.5/0.5 (SP)				
			Light gray to tannish gray fine quartz sand, scattered large shell fragments and whole shells in coarse gravel range, trace of silt. 10 YR 7.5/1-7.5/1.5 (SP)	100	2.0		2.5
-36.0	5.4					-35.6	5
			White to very light gray medium to fine quartz sand, traces of silt, clay and organic matter in collapsed burrow structures, scattered large white shell fragments in coarse gravel range. 10 YR 8.5/0.5-9/0.5 (SP)	100	8.0		7.5
						-40.6	10
				100			12.5
						-45.6	15
				100	16.0		
-48.0	17.4					-48.0	17.5
							20
						Composite 0-16.0 ft.	
						Final 4/1/03	
							22.5