

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1927487.730 Y=85529.200				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-148				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.4 Ft.			
9. TOTAL DEPTH OF HOLE 19.0 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.4	.0					-26.4	0
-27.7	1.3		Gray medium to fine quartz sand, abundant silt and clay in collapsed burrow structures. 10 YR 6/0.5-6.5/0.5 (SM)		0.5		
			Very light gray medium to fine quartz sand, trace of silt and clay in burrow structures. 10 YR 8/0.5-8.5/0.5 (SP)	100			2.5
						-31.4	5
					6.0		
				100			7.5
-36.3	9.9		Very light gray to white fine quartz sand. 10 YR 8.5/0.5 (SP)			-36.4	10
-37.7	11.3		Very light gray medium to fine quartz sand, few large shell fragments and whole shells in medium to coarse gravel range. 10 YR 8.5/0.5 (SP)	100			12.5
					14.0		
						-41.4	15
				100			17.5
-45.4	19.0					-45.4	
						Composite 0-18.0 ft.	20
						Final 3/24/03	
							22.5