

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1954998.810 Y=95040.260				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-151				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-17-02 12-17-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.5 Ft.			
9. TOTAL DEPTH OF HOLE 18.7 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.5	.0					-26.5	0
-28.4	1.9		White medium to fine quartz sand, few scattered shell fragments and whole shells in fine to medium gravel range. 10 YR 8.5/0.5 (SP)				
-30.3	3.8		Light gray medium to fine quartz sand, abundant large shell fragments in fine to coarse gravel range. 10 YR 7.5/1 (SP)	100	10	Mud-lined, sand filled crab burrow at 4.3-4.6 ft.	2.5
			Very light gray fine quartz sand, scattered inclusions of decayed organic matter and hurren structures. 10 YR 8/0.5 (SP)			-31.5	5
				100	8.0		7.5
						-36.5	10
				100			12.5
-40.5	14.0		Medium gray fine quartz sand. 10 YR 7/0.5 (SP)		14.0	-41.5	15
				100			17.5
-44.8	18.4		Gray quartz sand and abundant shell fragments. 10 YR 7/1 (SP)			-45.2	
-45.2	18.7					Composite 0-14.0 ft. Final 3/24/03	20
							22.5