

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1957038.900 Y=91983.320				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-154R2				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 0 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.8 Ft.			
9. TOTAL DEPTH OF HOLE 17.7 Ft.				18. TOTAL CORE RECOVERY FOR BORING 96 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.8	.0					-27.8	0
-29.7	1.9		Light gray to tannish gray medium to fine quartz sand, some shell fragments in fine to coarse gravel range, worm tubes. 10 YR 8/0.5-8/1.5 (SP)	100			2.5
			Very light gray to white medium to fine quartz sand, scattered shell fragments and whole shells in gravel range. 10 YR 8/0.5-8.5/0.5 (SP)			Large whole shell at 3.8-3.9 ft.	
						-32.6	5
				100			7.5
-36.6	10.8		Light gray medium to fine quartz sand. 10 YR 8/0.5 (SP)	100			10
-41.5	13.7		Gray to light gray medium to fine quartz sand, inclusions of gray decayed organic matter. 10 YR 7/0.5-7.5/0.5 (SP)			-42.6	15
-43.4	15.6		Gray fine quartz sand, trace of silt, few shell fragments. 10 YR 7/0.5-6.5/0.5 (SP)	100			17.5
-45.5	17.7					-45.5	
						No samples	20
						Final 3/24/03	
							22.5