

<b>DRILLING LOG</b>		DIVISION	INSTALLATION	SHEET 1 OF 1
1. PROJECT Baldwin County, AL: Olsen Associates		10. SIZE AND TYPE OF BIT 4" VIBRACORE		
2. LOCATION (Coordinates or Station) X=1851570.110 Y=74461.190		11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW		
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.		12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE		
4. HOLE NO. (As shown on drawing title and file number) BC-155		13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0		
5. NAME OF DRILLER G. Wiegman/A. Browder		14. TOTAL NUMBER OF CORE BOXES 2		
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED		15. ELEVATION GROUND WATER		
7. THICKNESS OF BURDEN 0 Ft.		16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02		
8. DEPTH DRILLED INTO ROCK 0 Ft.		17. ELEVATION TOP OF HOLE -24.9 Ft.		
9. TOTAL DEPTH OF HOLE 20.3 Ft.		18. TOTAL CORE RECOVERY FOR BORING 100 %		
		19. SIGNATURE OF G. Zarillo, SEA, Inc.		

ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-24.9	.0					-24.9	0
-26.0	1.1		Light gray medium to fine quartz sand, very abundant gray whole shells and shell fragments in fine to coarse gravel range. 10 YR 7.5/0.5 (SP)				
			Light gray fine quartz sand, few gray to tan shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100	10		2.5
						-28.8	5
				100	8.0		7.5
						-34.8	10
-36.4	11.5		Light gray fine quartz sand, few silt and clay inclusions, few scattered shell fragments in medium to coarse gravel range. 10 YR 7.5/0.5 (SP)	100			12.5
					15.0	-38.8	15
-41.8	17.0		Gray silty sand and clay. 10 YR 6/0.5 (SM)	100			17.5
-45.2	20.3					Composite 0-15.0 ft.	20
						Final 4/15/03	