

DRILLING LOG		DIVISION	INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates			10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1852609.910 Y=73477.160			11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.			12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-156			13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder			14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.			16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.			17. ELEVATION TOP OF HOLE -25.8 Ft.			
9. TOTAL DEPTH OF HOLE 20.2 Ft.			18. TOTAL CORE RECOVERY FOR BORING 100 %			
			19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS
-25.8	.0					-25.8
-26.8	1.1		Light tannish gray medium to fine quartz sand, few dark gray shell fragments in fine to medium gravel range. 10 YR 8/1 (SP)			
-28.8	3.1		Light gray medium to fine quartz sand, scattered tan to dark gray shell fragments in fine gravel range. 10 YR 7.5/0.5 (SP)	100	10	
			Light gray fine quartz sand, trace of shell fragments in fine to medium gravel range, trace of silt and clay in collapsed burrow structures. 10 YR 7.5/0.5 (SP)			
				100	8.0	
						-30.8
				100		
						-35.8
				100		
						-40.8
				100	16.0	
-43.8	18.0		Gray silty quartz sand. 10 YR 6/1 (SM)			
-46.0	20.2					Composite 0-16.0 ft.
						Final 4/15/03