

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1853145.000 Y=75434.900				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-157				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -25.8 Ft.			
9. TOTAL DEPTH OF HOLE 18.6 Ft.				18. TOTAL CORE RECOVERY FOR BORING 98 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-25.8	.0		Light gray fine quartz sand, scattered dark gray shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100	10	-25.8	0
-32.9	7.1		Light gray fine quartz sand, few scattered dark gray shell fragments in fine gravel range, trace of silt and clay in scattered collapsed burrows. 10 YR 7.5/0.5 (SP)	100	7.0	-30.8	5
-38.8	14.0		Tannish gray silty quartz sand. 10 YR 7/2.5 (SM)	100	13.0	Crushed shell layer at 9.9-10.1 ft. -35.8	10
-40.5	14.7		Light gray to tannish gray medium to fine quartz sand, some dark gray shell fragments. 10 YR 7.5/0.5-7.5/1.5 (SP)	100		-40.8	15
-42.2	16.4		Gray silty sand. 10 YR 6/0.5-6/1 (SM)	100		-44.4	17.5
-44.4	18.6					Composite 0-12.0 ft. Final 4/15/03	20
							22.5