

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1853621.300 Y=73871.420				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-158				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.5 Ft.			
9. TOTAL DEPTH OF HOLE 19.7 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.5	.0					-26.5	0
-27.8	1.3		Light gray medium to fine quartz sand, abundant gray, tan, and white shell fragments and whole shells in fine to coarse gravel range. 10 YR 7.5/0.5 (SP)	100	10		2.5
-31.5	5.0		Light gray medium to fine quartz sand, scattered gray to white shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100	40	-31.5	5
			Light gray fine quartz sand, trace of shell fragments in fine to medium gravel range, trace of silt and clay in collapsed burrow structures. 10 YR 7.5/0.5 (SP)	100			7.5
						-36.5	10
				100	120		12.5
-41.4	14.9		Brownish gray silt, some sand abundant shell fragments. 10 YR 6/1.5 (ML)	100		-41.5	15
							17.5
-46.2	19.7					-46.2 Composite 0-13.0 ft.	20
						Final 4/15/03	22.5