

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1854870.510 Y=75070.450				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-159				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -26.6 Ft.			
9. TOTAL DEPTH OF HOLE 19.1 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zerillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-26.6	.0					-26.6	0
-27.4	.8		Light gray fine quartz sand, abundant gray shell fragments in fine to medium gravel range. 10 YR 7.5/0.5 (SP)				
			Light gray fine quartz sand, trace of shell fragments and whole shells in fine to medium gravel range. 10 YR 7.5/0.5 (SP)	100	1.0		2.5
					4.0		
						-31.6	5
				100			7.5
-36.7	10.1					-36.6	10
			Light tannish gray fine quartz sand, trace of silt and clay in collapsed burrow structures. 10 YR 7/1.5-7.5/1.5 (SP)		11.0		
-39.6	13.0			100			12.5
-40.0	13.4		Tan silty quartz sand. 10 YR 7/2 (SM)				
			Light tannish gray fine quartz sand, some whole shells and shell fragments in fine to medium gravel range. 10 YR 7.5/0.5-7/2 (SP)			-41.6	15
-41.7	15.1						
			Tan to brown silty quartz sand, abundant large shell fragments. 10 YR 6/3 (SM)	100			17.5
-45.7	19.1					-45.7	
						Composite 0-11.0 ft.	20
						Final 4/15/03	
							22.5