

DRILLING LOG		DIVISION		INSTALLATION		SHEET 1 OF 1	
1. PROJECT Baldwin County, AL: Olsen Associates				10. SIZE AND TYPE OF BIT 4" VIBRACORE			
2. LOCATION (Coordinates or Station) X=1854885.710 Y=73882.560				11. DATUM FOR ELEVATION SHOWN (TBM or MSL) MLW			
3. DRILLING AGENCY AOSS/Olsen Associates, Inc.				12. MANUFACTURER'S DESIGNATION OF DRILL ALPINE PNEUMATIC VIBRACORE			
4. HOLE NO. (As shown on drawing title and file number) BC-160				13. TOTAL NO. OF OVERBURDEN SAMPLES TAKEN disturbed: 3 undisturbed: 0			
5. NAME OF DRILLER G. Wiegman/A. Browder				14. TOTAL NUMBER OF CORE BOXES 2			
6. DIRECTION OF HOLE <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED				15. ELEVATION GROUND WATER			
7. THICKNESS OF BURDEN 0 Ft.				16. DATE HOLE STARTED COMPLETED 12-20-02 12-20-02			
8. DEPTH DRILLED INTO ROCK 0 Ft.				17. ELEVATION TOP OF HOLE -27.0 Ft.			
9. TOTAL DEPTH OF HOLE 19.4 Ft.				18. TOTAL CORE RECOVERY FOR BORING 100 %			
				19. SIGNATURE OF G. Zarillo, SEA, Inc.			
ELEV.	DEPTH	LEGEND	CLASSIFICATION OF MATERIALS (Description)	CORE REC %	SAMPLE NUMBER	REMARKS	
-27.0	.0					-27.0	0
-28.8	1.8		Light gray medium to fine quartz sand, abundant gray, tan and white shell fragments in fine to coarse gravel range, trace of silt in burrow structures. 10 YR 7.5/0.5-8/0.5 (SP)	100	1.0		2.5
			Light gray to tannish gray fine quartz sand, trace of shell fragments in fine to medium gravel range. 10 YR 8/0.5-7.5/1.5 (SP)		4.0	Large whole shell at 3.8 ft.	
						-32.0	5
				100			7.5
						-37.0	10
					11.0		
-39.4	12.4		Grayish brown silt and some sand, shell fragments. 10 YR 6.5/1.5-6/1.5 (ML)	100			12.5
						-42.0	15
				100			17.5
-46.4	19.4					-46.4	20
						Composite 0-11.0 ft.	
						Final 4/15/03	
							22.5