

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Baldwin County, AL 2006 Phase I Sand Search Baldwin County, Alabama			9. SIZE AND TYPE OF BIT 4.0 In.	
2. BORING DESIGNATION BC06-14			10. COORDINATE SYSTEM/DATUM State Plane AL	
LOCATION COORDINATES X = 1,947,633 Y = 97,573			HORIZONTAL NAD 1983	
3. DRILLING AGENCY Olsen Associates, Inc			11. MANUFACTURER'S DESIGNATION OF DRILL Pneumatic	
CONTRACTOR FILE NO.			<input type="checkbox"/> AUTO HAMMER <input type="checkbox"/> MANUAL HAMMER	
4. NAME OF DRILLER Alpine Ocean Seismic Survey Inc			12. TOTAL SAMPLES	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			DISTURBED	
DEG. FROM VERTICAL			UNDISTURBED (UD)	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			13. TOTAL NUMBER CORE BOXES 2	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			14. ELEVATION GROUND WATER	
8. TOTAL DEPTH OF BORING 20.2 Ft.			15. DATE BORING 05-01-06	
			STARTED 05-01-06	
			COMPLETED 05-01-06	
			16. ELEVATION TOP OF BORING -10.3 Ft.	
			17. TOTAL RECOVERY FOR BORING 20.2 Ft.	
			18. SIGNATURE AND TITLE OF INSPECTOR Gary Zarillo, PG	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-10.3	0.0					
					1.0	Sample #1.0, Depth = 1.0'
					6.0	Sample #6.0, Depth = 6.0'
			White fine quartz sand, trace of white shell fragments in fine gravel range, few scattered inclusions of gray clay in collapsed burrows, (10YR-8.5/1), (SP).		12.0	Sample #12.0, Depth = 12.0'
-23.6	13.3					
					17.0	Sample #17.0, Depth = 17.0'
-28.4	18.1		Light gray fine quartz sand, scattered inclusions of gray clay in burrow linings and collapsed burrows, (10YR-7.5/1), (SP).		Comp 1	Sample #Comp 1, Depth = 18.5' Comp 1 (0-12.0')
-30.6	20.3		Brownish gray silty quartz sand, (10YR-6.5/2), (SM).		Comp 2	Sample #Comp 2, Depth = 20.0' Comp 2 (0-17.0')
			End of Boring			

FLORIDA DEP ROSS OLSEN BALDWIN_FINAL.GPJ FL DEP ROSS.GDT 9/25/06