

DRILLING LOG		DIVISION	INSTALLATION	SHEET 1 OF 1 SHEETS
1. PROJECT Baldwin County, AL 2006 Phase I Sand Search Baldwin County, Alabama			9. SIZE AND TYPE OF BIT 4.0 In.	
2. BORING DESIGNATION BC06-28			10. COORDINATE SYSTEM/DATUM State Plane AL	
LOCATION COORDINATES X = 1,904,718 Y = 68,141			HORIZONTAL NAD 1983	
3. DRILLING AGENCY Olsen Associates, Inc			11. MANUFACTURER'S DESIGNATION OF DRILL <input type="checkbox"/> AUTO HAMMER Pneumatic <input type="checkbox"/> MANUAL HAMMER	
CONTRACTOR FILE NO.			12. TOTAL SAMPLES	
4. NAME OF DRILLER Alpine Ocean Seismic Survey Inc			13. TOTAL NUMBER CORE BOXES 2	
5. DIRECTION OF BORING <input checked="" type="checkbox"/> VERTICAL <input type="checkbox"/> INCLINED			14. ELEVATION GROUND WATER	
DEG. FROM VERTICAL			15. DATE BORING STARTED 05-01-06 COMPLETED 05-01-06	
6. THICKNESS OF OVERBURDEN 0.0 Ft.			16. ELEVATION TOP OF BORING -34.1 Ft.	
7. DEPTH DRILLED INTO ROCK 0.0 Ft.			17. TOTAL RECOVERY FOR BORING 20.2 Ft.	
8. TOTAL DEPTH OF BORING 20.2 Ft.			18. SIGNATURE AND TITLE OF INSPECTOR Gary Zarillo, PG	

ELEV. (ft)	DEPTH (ft)	LEGEND	CLASSIFICATION OF MATERIALS Depths and elevations based on measured values	% REC.	BOX OR SAMPLE	REMARKS
-34.1	0.0					
			Very light gray to white fine quartz sand, scattered gray, tan, and white shell fragments in fine to medium gravel range, scattered whole shells in medium to coarse gravel range, (10YR-8.5/1), (SP).		1.0	Sample #1.0, Depth = 1.0'
					3.0	Sample #3.0, Depth = 3.0'
-40.2	6.1				6.0	Sample #6.0, Depth = 6.0'
-41.7	7.6		Light gray fine quartz sand, white to gray shell fragments in fine to medium gravel range, scattered whole shells in medium to coarse gravel range, inclusions of gray clay at 6.1-6.6 ft, white (10YR-8/1), (SP).		Comp	Sample #Comp, Depth = 7.0' Comp (0-7.0')
			Gray silt, some gray clay, trace of iron stained fine quartz sand, grayish brown (10YR-5/2), (ML).			
-54.3	20.2					
			End of Boring			

FLORIDA DEP ROSS OLSEN BALDWIN_FINAL.GPJ FL DEP ROSS.GDT 9/25/06